

### FEATURES



- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss ,high efficiency
- High current capability ,low forward voltage drop
- High surge capability
- Very low profile-typical height of 1.1mm
- Ideal for automated placement
- High temperature soldering guaranteed:260°C/10 seconds at terminals
- Component in accordance to RoHS 2015/863/EU



### MECHANICAL DATA

- Case: TO-277 molded plastic body
- Terminals: Plated axial leads, solderable per MIL-STD-750,method 2026
- Mounting Position: Any
- Weight: 0.092 grams(approx)

### TO-277



Dimensions in inches and (millimeters)

### TYPICAL APPLICATIONS

For use in low voltage ,high frequency inverters ,DC/DC converters, free wheeling ,and polarity protection applications

### MAXIMUM RATINGS

(Ratings at 25°C ambient temperature unless otherwise specified )

Parameter	Symbol	Value	Unit
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	250	V
Maximum average forward rectified current	I <sub>F(AV)</sub>	5.0	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method at rated TL)	I <sub>FSM</sub>	120	A
Operating junction temperature range	T <sub>J</sub>	-55 to+150	°C
Storage temperature range	T <sub>stg</sub>	-55 to+150	°C

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub>=25°C Unless otherwise noted)

Parameter	Test Conditions		Symbol	Typ.	Max.	Unit
Instantaneous forward voltage	I <sub>F</sub> =5.0A	T <sub>J</sub> =25°C	V <sub>F</sub> 1)	0.84	0.95	V
		T <sub>J</sub> =100°C		0.73	-	
		T <sub>J</sub> =125°C		0.69	-	
	I <sub>F</sub> =2.0A	T <sub>J</sub> =25°C		0.78	-	
		T <sub>J</sub> =100°C		0.66	-	
		T <sub>J</sub> =125°C		0.62	-	
Reverse current	V <sub>R</sub> =250V	T <sub>J</sub> =25°C	I <sub>R</sub> 2)	0.1	5.0	μA
		T <sub>J</sub> =100°C		0.1	-	mA
		T <sub>J</sub> =125°C		0.5	-	
Typical junction capacitance	4V,1MHz		C <sub>J</sub>	90		pF

Notes: 1.Pulse test: 300 μs pulse width,1% duty cycle  
2.Pulse test: pulse width ≤40ms

## THERMAL CHARACTERISTICS

Reverse recovery time

Parameter	Symbol	TO-277	Unit
Typical thermal resistance <sup>3)</sup>	R <sub>θJA</sub>	60.0	°C/W
	R <sub>θJL</sub>	3.0	

3 Units mounted on recommended PCB 1 oz. Pad layout

## AVAILABLE PACK INFORMATION

Product code	Pack	Carton Size L×W×H(mm)	Inner Box Size L×W×H(mm)	Reel diameter (mm)	Inner Box Number	Reel Number Per A Inner Box	Part Number Per A Reel(K)	Quantity(carton) (K)
Sp5250 TO-277	Reel	370×370×360	338×338×39	φ330	7	2	5	70

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS





FIG.5-TYPICAL JUNCTION CAPACITANCE



## Friendship Reminder

- JiNan JingHeng (hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.
- JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of JH.
- JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.